

## NOTES:

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.

2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.

 $\stackrel{\frown}{3}$  N IS THE TOTAL NUMBER OF TERMINALS.

AND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE, RESPECTIVELY.

🖒 DIMENSION 6 APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.20mm AND 0.25mm FROM TERMINAL TIP.

THE PIN #1 IDENTIFIER MUST BE LOCATED ON THE TOP SURFACE OF THE PACKAGE WITHIN HATCHED AREA AS SHOWN, EITHER AN INDENTATION MARK OR INK/LASER MARK IS ACCEPTABLE.

7. PACKAGE WARPAGE MAX 0.10mm.

 $\stackrel{\sim}{\gg}$  APPLIES TO EXPOSED PAD AND TERMINALS, EXCLUDES INTERNAL DIMENSION OF EXPOSED PAD.

9 DRAWING CONFORMS TO JEDEC MO-220.

MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.

11. NUMBER OF LEADS SHOWN ARE FOR REFERENCE ONLY.

APPLICABLE ONLY FOR PACKAGES WITH TIGHT CORNER LEADS METAL TO METAL CLEARANCE AS DEFINED IN JEDEC.

13. MATERIAL MUST BE COMPLIANT WITH MAXIM SPECIFICATION 10-0131 FOR SUBSTANCE CONTENT, MUST BE EU ROHS COMPLIANT WITHOUT EXEMPTION AND PB-FREE.

14. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND POFREE (+) PKG. CODES.

S M B O L	56L 8x8			
Bo	NIN NOV		MAY	No <sub>TE</sub>
L	MIN.	NOM.	MAX.	΄Ε
Α	0.70	0.75	0.80	
A1	0.00	0.02	0.05	
A2	0.20 REF			
b	0.20 0.25		0.30	5
С	0.12 X 45° REF.			
D	7.90	8.00	8.10	
Ε	7.90	8.00	8.10	
е	0.50 BSC			
N	56			3
ND	14			4
NE	14			4
L	0.30	0.40	0.50	
L4	0.31 REF.			
k	0.25	-		

PKG.		D2			E2	
CODE	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
T5688+2	6.50	6.65	6.70	6.50	6.65	6.70
T5688+3	6.50	6.65	6.70	6.50	6.65	6.70
T5688+2C	6.50	6.65	6.70	6.50	6.65	6.70
T5688+4C	6.50	6.65	6.70	6.50	6.65	6.70
T5688M+3	6.50	6.65	6.70	6.50	6.65	6.70
T5688MN+3	6.50	6.65	6.70	6.50	6.65	6.70
T5688MK+2	6.50	6.65	6.70	6.50	6.65	6.70
T5688+5	6.50	6.65	6.70	6.50	6.65	6.70
T5688+6	4.60	4.70	4.80	4.60	4.70	4.80
T5688+6C	4.60	4.70	4.80	4.60	4.70	4.80

VA	RIATION fo	r T5688+6,	T5688+6C
41	0.00	0.035	0.05

	axim tegrated <sub>™</sub>
--	-------------------------------

**JEDEC** 

WLLD-5 WLLD-5 WLLD-5 WLLD-5 WLLD-5 WLLD-5 WLLD-5 WLLD-5 WLLD-5

TITLE:

EXPOSED PAD VARIATION

PACKAGE DUTLINE, 56L THIN QFN, 8×8×0.75mm

APPROVAL DOCUMENT CONTROL NO. CHUCK XIA 21-0135

REV.