

DEMO MANUAL EVAL-LT8355-1-AZ

LT8355-1 60V_{IN}/120V_{OUT} Dual LED Controller with SSFM

DESCRIPTION

Evaluation board EVAL-LT8355-1-AZ is a high voltage dual LED controller featuring the LT®8355-1. Channel 1 is assembled as a boost LED driver and channel 2 as a buck-boost mode LED driver. Either channel can be altered to a boost LED driver or buck-boost mode LED driver by adjusting the FB network and LED connection. EVAL-LT8355-1-AZ drives a single string of LEDs per channel when the input is between 8V and 18V. Channel 1 drives up to 72V of LEDs at 450mA and channel 2 drives up to 30V of LEDs at 1A. EVAL-LT8355-1-AZ has an undervoltage lockout (UVLO) set at 6.2V falling and 7.5V rising. EVAL-LT8355-1-AZ features PWM dimming, analog dimming, shutdown, open LED and short LED fault protection and reporting.

EVAL-LT8355-1-AZ runs at 250kHz switching frequency and features spread spectrum frequency modulation (SSFM) modulating its switching frequency from 250kHz to 310kHz to reduce EMI emissions. Small ceramic input and output capacitors are used to save space and cost. A high voltage 100V external power switch and 100V catch diode are used on each channel for up to 32W boost output for channel 1 and up to 30W buck-boost mode output for channel 2 as assembled. The open LED overvoltage protection (OVP) uses the IC's constant voltage regulation loop to limit the LED+ to LED– voltage if the LED string is opened to approximately 81V for channel 1 and 36V for channel 2.

The input and output filters on EVAL-LT8355-1-AZ help further reduce its EMI. These filters consist of a small ferrite bead or inductor and high frequency ceramic capacitors. A small resistor on the gate pin of the power MOSFET is used to reduce high frequency EMI. These filters, combined with proper board layout and SSFM, are very effective in reducing EMI to comply with CISPR25 class 5 limits. Please follow the recommended layout and the four-layer PCB thickness of EVAL-LT8355-1-AZ. For best efficiency and PWM dimming performance, the EMI filters can be removed. The LT8355-1's integrated PWMTG high-side PMOS drivers assist with PWM dimming of the connected LEDs. The LED strings can be PWM-dimmed for accurate brightness control with externally generated PWM signals for highest achievable dimming ratios. They can also utilize LT8355-1's internally generated PWM feature for up to 128:1 exponential dimming. When running PWM dimming, the SSFM aligns itself with the PWM signal for flicker-free operation of each channel's LED string. This applies to both internal and external PWM dimming. The LT8355-1 uses CTRL1 analog dimming for channel 1, and CTRL2 and IADJ2 pins for two-pin analog dimming for channel 2.

The input undervoltage lockout (UVLO), LED current, output overvoltage protection (OVP), and switching frequency, can all be easy adjusted with simple resistor changes to EVAL-LT8355-1-AZ. Modifications can be made to convert the channels to boost, buck-boost mode and buck mode LED drivers, and maintain low EMI, PWM dimming and fault diagnostic features. Buck mode, buck-boost mode and boost LED driver schematics are provided in the data sheet. Please consult the data sheet or the applications team regarding how to customize EVAL-LT8355-1-AZ.

The LT8355-1 data sheet gives a complete description of the part, operation, and applications information. The data sheet must be read in conjunction with this demo manual for evaluation board EVAL-LT8355-1-AZ. The LT8355IUFDM-1 is assembled in a 28-lead side solderable plastic QFN package with a thermally enhanced exposed ground pad and is AEC-Q100 qualified for automotive applications. Proper board layout is essential for maximum performance. See the data sheet section "Designing the Printed Circuit Board".

Design files for this circuit board are available.

All registered trademarks and trademarks are the property of their respective owners.

BOARD PHOTO



Figure 1. EVAL-LT8355-1-AZ Demo Board

PERFORMANCE SUMMARY Specifications are at T_A = 25°C

PARAMETER	CONDITION	MIN	ТҮР	MAX	UNITS
Input Voltage PVIN Range	Operating	8		18	V
Switching Frequency (f _{SW} , 100% to 125% SSFM)	R40 = 86.6k	250		312	kHz
ILED	$8V < PVIN < 18V, CTRL1, CTRL2, ADJ2 Turrets = Float CH1: RS2 = 0.56 \Omega, V_{LED} \leq 72V$ CH2: RS4 = 0.25 Ω , V_{LED} $\leq 30V$		450 1		mA A
Open LED Protection (LED+ to LED-)	CH1: R14 = 0, R11 = 1M, R10 = 15k CH2: R52 = 287k, R53 = 10k, R47 = 10k		81 36		V V
Peak Efficiency (SSFM ON)	PVIN = 12V, CH1: V_{LED} = 72V, I_{LED} = 450mA, CH2: V_{LED} = 30V, I_{LED} = 1A with Filters without Filters		90 91		%
Peak Switch Current Limit	CH1: RS1 = 0.013Ω CH2: RS3 = 0.012Ω		7.7 8.3		AA
Internally-Generated PWM Dimming Range	0.5V < V _{PWM} < 1.5V	1/128		100	%
Internally-Generated PWM Dimming Frequency	R40 = 86.6k		250		Hz
PV _{IN} Undervoltage Lockout (UVLO) Falling	R33 = 499k, R34 = 127k		6.2		V
PV _{IN} Enable Turn-On (EN) Rising			7.5		V

QUICK START PROCEDURE

Evaluation board EVAL-LT8355-1-AZ is easy to set up to evaluate the performance of the LT8355-1. Follow the procedure below.

- With power off, connect a string of LEDs that will run with forward voltage less than or equal to 72V (at 450mA) to the LED1+ and LED1- (boost) turrets and another string of LEDs that will run with forward voltage less than or equal to 30V (at 1A) to the LED2+ and LED2- (buck-boost) turrets as shown in Figure 2.
- 2. With power off, connect the input power supply to the PVIN and GND turrets. Make sure that the DC input voltage will not exceed 18V.
- 3. Turn the input power supply on and make sure the voltage is between 8V and 18V for proper operation at max LED current.
- 4. Observe the LED strings running at the programmed LED current.

- 5. To change the brightness with **analog dimming**, the CTRL1 pin is used for channel 1 and CTRL2 and IADJ2 pins are used for channel 2. The product of the offset CTRL and IADJ pin voltages sets the current when the two voltages vary between 0.5V and 1.5V. Please refer to data sheet for more details.
- 6. To change the brightness with **external PWM dimming**, attach a rectangular waveform with varying duty cycle to the respective PWM turret for channel 1 and channel 2. The ON and OFF voltages should be above 1.6V and below 0.4V, respectively.
- To change the brightness with internally-generated PWM dimming, adjust the voltage at the respective PWM pin for channel 1 and channel 2 between 0.5V and 1.5V to vary the duty ratio of the internal PWM generator.

QUICK START PROCEDURE



Figure 2. Setup Drawing for EVAL-LT8355-1-AZ: Channel 1 as Boost LED Driver, and Channel 2 as Buck-Boost Mode LED Driver (See Boost LED Driver Setup Section for More Information on Boost Topology)

START-UP WITH LOW VISP TO VISA

Full-scale LED current sense threshold voltage (V_{ISP} to V_{ISN}) for LT8355-1 is 250mV, which sets full-scale LED current according to Equation 1.

$$I_{\text{LED}} = \frac{1}{4 \cdot R_{\text{ILED}}} A \tag{1}$$

The LED current sense threshold voltage can be trimmed to be lower than 250mV when analog dimming is desired. This includes but is not limited to, when a single sense resistor is used for multiple designs with different current levels needed for each design, and when low current level is required at start-up and increases at steady state, etc.

For configurations where the LED current sense threshold (V_{ISP} to V_{ISN}) is configured for 120mV or lower via CTRL or IADJ pin, an additional resistor connecting V_{REF} to FB is needed to allow for proper start-up of the LT8355-1 (see Figure 3). Refer to data sheet for more information. See Equation 2 and Equation 3 to set resistor values for boost and buck-boost mode topologies.



Figure 3. Proper Start-Up Configuration

Boost: Calculate R1 and R2 to set desired V_{OUT_OVP} voltage and V_{FB} to 400mV at $V_{IN_MIN}.$

$$V_{IN_MIN} = 400 \text{mV} + \left(40 \mu \text{A} - \frac{1.6 \text{V}}{\text{R1}}\right) \text{R2}$$

$$V_{OUT_OVP} = 1.2 \text{V} + \left(120 \mu \text{A} - \frac{800 \text{mV}}{\text{R1}}\right) \text{R2}$$
(2)

Buck-Boost: Calculate R3 to set V_{LED_OVP} ($V_{OUT} - V_{IN}$) to desired OVP voltage.

$$V_{\text{LED}_{\text{OVP}}} = V_{\text{BE}} + 100\mu\text{A} \bullet \text{R3}$$
(3)

BOOST LED DRIVER SETUP

EVAL-LT8355-1-AZ has channel 1 assembled as a boost LED driver and channel 2 as a buck-boost mode LED driver. With minor adjustments channel 2 can be reconfigured as a boost LED driver. In buck-boost mode, the LED-connection is at V_{IN}, and a level shifter is used for the FB network. In a boost LED driver, the LED-connection is at GND and a resistor divider is used for the FB network.

To configure EVAL-LT8355-1-AZ channel 2 as a boost LED driver, remove R53, R52, Q2, FB10, C38 and C49. Install 0Ω for R46 and 1M for R48. Consult the data sheet for OVP calculations and details about the FB pin. Connect the LED string from LED+ to LED– (GND boost).

Note that when EVAL-LT8355-1-AZ is reconfigured as a boost LED driver, other components may need to be adjusted depending on their voltage rating and power capabilities.

TEST RESULTS







Figure 5. EVAL-LT8355-1-AZ, Internal 250Hz 10% PWM Dimming with EMI Filters: $12V_{IN},$ Channel 1, $72V_{LED}$ 450mA, Channel 2, $30V_{LED}$ 1A



Figure 6. EVAL-LT8355-1-AZ, External 150Hz PWM Dimming with EMI Filters: 12V_{IN}, Channel 1, 72V_{LED} 450mA, Channel 2, 30V_{LED} 1A

TEST RESULTS



Figure 7. EVAL-LT8355-1-AZ: 50% to 100% to 50% Load Step Transient Response, $12V_{IN}$





TEST RESULTS



Figure 9. Conducted Emissions (Voltage Method): 12V_{IN}, Channel 1, 72V_{LED} 450mA, Channel 2, 30V_{LED} 1A



Figure 10. Conducted Emissions (Current Method): 12V_{IN}, Channel 1, 72V_{LED} 450mA, Channel 2, 30V_{LED} 1A



EMISSIONS SHIELD (OPTION)

For the lowest emissions, an EMI shield can be attached to EVAL-LT8355-1-AZ. The PCB was fabricated with placeholders for six shield clips that can hold a 61.5mm × 61.5mm metal shield. Part number for an example shield can be found in the Parts List section in the Optional EMI Filter Components section. The top silkscreen (Figure 12) shows the placeholders for the six-surface mount shield clips. Emissions can be tested with and without the removable clip shield.



Figure 12. EVAL-LT8355-1-AZ Top Silkscreen Outlining Placement of Shield Clips and EMI Shield on PCB

PARTS LIST

ITEM	QTY	REFERENCE	PART DESCRIPTION	MANUFACTURER/PART NUMBER
Required	Circuit Cor	nponents		
1	2	C3, C29	CAP., 100µF, ALUM ELECT, 25V, 20%, 6.3mm × 7.7mm, D8, SMD, RADIAL, EEEHA, AEC-Q200	PANASONIC, EEEHAE101XAP
2	1	C7	CAP., 1µF, X7R, 25V, 10%, 0805, AEC-Q200	TDK, CGA4J3X7R1E105K125AB
3	1	C8	CAP., 1000pF, X7R, 50V, 10%, 0402, AEC-Q200	MURATA, GCM155R71H102KA37D
4	4	C9-C11, C36	CAP., 4.7µF, X7S, 100V, 10%, 1210, AEC-Q200	MURATA, GCM32DC72A475KE02L
5	2	C14, C42	CAP., 2.2µF, X5R, 25V, 10%, 0603, AEC-Q200	TAIYO YUDEN, TMK107BBJ225KAHT
6	4	C22, C23, C31, C32	CAP., 4.7µF, X7R, 25V, 10%, 1210, AEC-Q200	TAIYO YUDEN, TMF325B7475KMHP
7	1	C33	CAP., 2.2µF, X5R, 10V, 10%, 0603, AEC-Q200	TAIYO YUDEN, LMK107BJ225KAHT
8	1	C34	CAP., 680pF, X7R, 50V, 10%, 0402, AEC-Q200	TDK, CGA2B2X7R1H681K050BA
9	1	C35	CAP., 4.7µF, X5R, 10V, 10%, 0603, AEC-Q200	TAIYO YUDEN, LMK107BJ475KAHT
10	1	C38	CAP., 10µF, X7S, 50V, 10%, 1210, AEC-Q200, NO SUBS ALLOWED	MURATA, GCM32EC71H106KA03L
11	2	D1, D4	DIODE, SCHOTTKY, 100V, 3A, POWERDI5, AEC-Q101	DIODES INC., PDS3100Q-13
12	1	L2	IND., 15μH, PWR, SHIELDED, 20%, 7.7A, 50.29mΩ, 4040DD, IHLE-5A, AEC-Q200	VISHAY, IHLE4040DDER150M5A
13	1	L4	IND., 10μH, PWR, SHIELDED, 20%, 8.5A, 33.06mΩ, 4040DD, IHLE-5A SERIES, AEC-Q200	VISHAY, IHLE4040DDER100M5A
14	2	M1, M9	XSTR., MOSFET, N-CH, 100V, 37A, POWERPAK SO-8L, AEC-Q101	VISHAY, SQJA72EP-T1_GE3
15	2	M4, M10	XSTR., MOSFET, P-CH, 100V, 33.6A, POWERPAK SO-8L, AEC-Q101	VISHAY, SQJ211ELP-T1_GE3
16	1	Q2	XSTR., PNP, 100V, 1A, SOT-23-3, AEC-Q101	DIODES INC., FMMT593QTA
17	3	R1, R35, R36	RES., 100k, 1%, 1/16W, 0402, AEC-Q200	VISHAY, CRCW0402100KFKED
18	4	R5, R13, R39, R43	RES., 100k, 5%, 1/16W, 0402, AEC-Q200	VISHAY, CRCW0402100KJNED
19	1	R8	RES., 39k, 1%, 1/16W, 0402, AEC-Q200	YAGEO, AC0402FR-0739KL
20	2	R9, R49	RES., 10Ω, 5%, 1/16W, 0402, AEC-Q200	VISHAY, CRCW040210R0JNED
21	1	R10	RES., 15k, 1%, 1/16W, 0402, AEC-Q200	YAGEO, AC0402FR-0715KL
22	1	R11	RES., 1M, 1%, 1/10W, 0603	VISHAY, CRCW06031M00FKEA
23	1	R14	RES., 0Ω, 1/10W, 0402, AEC-Q200	PANASONIC, ERJ2GEOR00X
24	1	R33	RES., 499k, 1%, 1/10W, 0603, AEC-Q200	VISHAY, CRCW0603499KFKEA
25	1	R34	RES., 127k, 1%, 1/16W, 0402, AEC-Q200	VISHAY, CRCW0402127KFKED
26	1	R40	RES., 86.6k, 1%, 1/10W, 0603, AEC-Q200	VISHAY, CRCW060386K6FKEA
27	1	R42	RES., 30k, 1%, 1/16W, 0402, AEC-Q200	VISHAY, CRCW040230K0FKED
28	1	R47	RES., 10k, 1%, 1/10W, 0402, AEC-Q200	PANASONIC, ERJ2RKF1002X
29	1	R52	RES., 287k, 1%, 1/16W, 0402, AEC-Q200	VISHAY, CRCW0402287KFKED
30	1	R53	RES., 10k, 5%, 1/16W, 0402, AEC-Q200	VISHAY, CRCW040210K0JNED
31	1	RS1	RES., 0.013Ω, 1%, 1W, 1206, LONG-SIDE TERM, SENSE, AEC-Q200	ROHM, LTR18EZPFSR013
32	1	RS2	RES., 0.56Ω, 1%, 1/2W, 1206, SENSE, AEC-Q200	PANASONIC, ERJ8BQFR56V
33	1	RS3	RES., 0.012Ω, 1%, 1.5W, 1206, LONG-SIDE TERM, METAL, SENSE, AEC-Q200	KOA SPEER, WU732B15TTD12L0F
34	1	RS4	RES., 0.25Ω, 1%, 1/2W, 1206, SENSE, AEC-Q200	YAGEO, PT1206FR-7W0R25L
35	1	U1	IC, DUAL LED CONTROLLER, QFN-28, AEC-Q100	ANALOG DEVICES, LT8355IUFDM-1#WPBF

PARTS LIST

ITEM	QTY	REFERENCE	PART DESCRIPTION	MANUFACTURER/PART NUMBER
Optional E	EMI Filter	Components	·	·
36	0	C1, C27	CAP., OPTION, 0402	
37	0	C2, C28	CAP, OPTION, 1206	
38	4	C5, C6, C30, C45	CAP., 10µF, X7R, 25V, 10%, 1210, AEC-Q200	TDK, CGA6P1X7R1E106K250AC
39	2	C15, C43	CAP., 0.1µF, X7S, 100V, 10%, 0603, AEC-Q200	TDK, CGA3E3X7S2A104K080AB
40	0	C19-C21, C47, C48	CAP, OPTION, 0603	
41	1	C49	CAP., 0.1µF, X7R, 50V, 10%, 0603, AEC-Q200	TDK, CGA3E2X7R1H104K080AA
42	3	FB4, FB9, FB10	IND., 330Ω AT 100MHz, FERRITE BEAD, 25%, 1.8A, 80mΩ, 0805, 1LN	TAIYO YUDEN, FBMH2012HM331-T
43	0	FB5	IND., FERRITE BEAD, OPT, 0805	
44	2	L1, L3	IND., 8.2μH, PWR, SHIELDED, 20%, 8A, 26.4mΩ, 6.56mm × 6.36mm, XAL6060, AEC-Q200	COILCRAFT, XAL6060-822MEC
45	2	R7, R41	RES., 10Ω, 5%, 1/10W, 0603, AEC-Q200	VISHAY, CRCW060310R0JNEA
46	0	CL1-CL6	OPTION, WE-SHC CABINET CLIP 6.5mm × 0.8mm × 1.27mm	WURTH, 369 000 00
47	0	SH1	OPTION, WE-SHC SHIELDIY 61.5mm × 61.5mm	WURTH, 360002
Optional E	Electrical (Components	·	
48	0	C17, C18, C25, C41, C46, C50, C51	CAP., OPTION, 0402	
49	0	C12, C13, C16, C37, C39, C40, C44	CAP, OPTION, 1210	
50	0	C24	CAP., OPTION, ALUM. ELECT., SMD	
51	0	D2, D3, D5, D6	DIODE, OPTION, SOD-323F	
52	0	FB1-FB3, FB6-FB8	IND., OPTION, FERRITE BEAD, 1210	
53	0	Q1	XSTR., OPTION, PNP, SOT-23	
54	0	R3, R6, R12, R19- R22, R25, R32, R37, R38, R44-R46, R50, R51, R59	RES., OPTION, 0402	
55	0	R48	RES., OPTION, 0603	
Hardware	: For Dem	o Board Only		
56	10	E1-E4, E8-E13	TEST POINT, TURRET, 0.094" MTG. HOLE, PCB 0.062" THK	MILL-MAX, 2501-2-00-80-00-00-07-0
57	5	E14-E18	TEST POINT, TURRET, 0.064" MTG. HOLE, PCB 0.062" THK	MILL-MAX, 2308-2-00-80-00-07-0
58	2	J1, J2	CONN., BANANA JACK, FEMALE, THT, NON-INSULATED, SWAGE, 0.218"	KEYSTONE, 575-4
59	4	MP1-MP4	STANDOFF, NYLON, SNAP-ON, 0.50"	KEYSTONE, 8833

SCHEMATIC DIAGRAM



NOTES: UNLESS OTHERWISE SPECIFIED. 1. ALL RESISTORS 5%, 0402. 2. ALL CAPACITORS 0603.

SCHEMATIC DIAGRAM



NOTES: UNLESS OTHERWISE SPECIFIED. 1. ALL RESISTORS 5%, 0402. 2. ALL CAPACITORS 0603.

REVISION HISTORY

REV	DATE	DESCRIPTION	PAGE NUMBER
А	02/24	Updated Start-Up with Low V _{ISP} to V _{ISN} section.	5

Rev. A

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.



ESD Caution

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

Legal Terms and Conditions

By using the evaluation board discussed herein (together with any tools, components documentation or support materials, the "Evaluation Board"), you are agreeing to be bound by the terms and conditions set forth below ("Agreement") unless you have purchased the Evaluation Board, in which case the Analog Devices Standard Terms and Conditions of Sale shall govern. Do not use the Evaluation Board until you have read and agreed to the Agreement. Your use of the Evaluation Board shall signify your acceptance of the Agreement. This Agreement is made by and between you ("Customer") and Analog Devices, Inc. ("ADI"), with its principal place of business at One Technology Way, Norwood, MA 02062, USA. Subject to the terms and conditions of the Agreement, ADI hereby grants to Customer a free, limited, personal, temporary, non-exclusive, non-sublicensable, non-transferable license to use the Evaluation Board FOR EVALUATION PURPOSES ONLY. Customer understands and agrees that the Evaluation Board is provided for the sole and exclusive purpose referenced above, and agrees not to use the Evaluation Board for any other purpose. Furthermore, the license granted is expressly made subject to the following additional limitations: Customer shall not (i) rent, lease, display, sell, transfer, assign, sublicense, or distribute the Evaluation Board; and (ii) permit any Third Party to access the Evaluation Board. As used herein, the term "Third Party" includes any entity other than ADI, Customer, their employees, affiliates and in-house consultants. The Evaluation Board is NOT sold to Customer; all rights not expressly granted herein, including ownership of the Evaluation Board, are reserved by ADI. CONFIDENTIALITY. This Agreement and the Evaluation Board shall all be considered the confidential and proprietary information of ADI. Customer may not disclose or transfer any portion of the Evaluation Board to any other party for any reason. Upon discontinuation of use of the Evaluation Board or termination of this Agreement, Customer agrees to promptly return the Evaluation Board to ADI. ADDITIONAL RESTRICTIONS. Customer may not disassemble, decompile or reverse engineer chips on the Evaluation Board. Customer shall inform ADI of any occurred damages or any modifications or alterations it makes to the Evaluation Board, including but not limited to soldering or any other activity that affects the material content of the Evaluation Board. Modifications to the Evaluation Board must comply with applicable law, including but not limited to the RoHS Directive. TERMINATION. ADI may terminate this Agreement at any time upon giving written notice to Customer agrees to return to ADI the Evaluation Board that time. LINITATION OF LIABILITY. THE EVALUATION BOARD PROVIDED HEREUNDER IS PROVIDED "AS IS" AND ADI MAKES NO WARRANTIES OR REPRESENTATIONS OF ANY KIND WITH RESPECT TO IT. ADI SPECIFICALLY DISCLAIMS ANY REPRESENTATIONS, ENDORSEMENTS, GUARANTEES, OR WARRANTIES, EXPRESS OR IMPLIED, RELATED TO THE EVALUATION BOARD INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, TITLE, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. IN NO EVENT WILL ADI AND ITS LICENSORS BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES RESULTING FROM CUSTOMER'S POSSESSION OR USE OF THE EVALUATION BOARD, INCLUDING BUT NOT LIMITED TO LOST PROFITS, DELAY COSTS, LABOR COSTS OR LOSS OF GOODWILL. ADI'S TOTAL LIABILITY FROM ANY AND ALL CAUSES SHALL BE LIMITED TO THE AMOUNT OF ONE HUNDRED US DOLLARS (\$100.00). EXPORT. Customer agrees that it will not directly or indirectly export the Evaluation Board to another country, and that it will comply with all applicable United States federal laws and regulations relating to exports. GOVERNING LAW. This Agreement shall be governed by and construed in accordance with the substantive laws of the Commonwealth of Massachusetts (excluding conflict of law rules). Any legal action regarding this Agreement will be heard in the state or federal courts having jurisdiction in Suffolk County, Massachusetts, and Customer hereby submits to the personal jurisdiction and venue of such courts. The United Nations Convention on Contracts for the International Sale of Goods shall not apply to this Agreement and is expressly disclaimed.

14

